

FLOOR & CEILING TYPE

AIR CONDITIONING



MODEL: DCR-IV / CR-IV



FILTER



4 -SPEED FAN
LEVELS



2 WAYS AUTO SWING



SLEEP MODE



TIMER



Standard



Option




คอมเพรสเซอร์
WARRANTY 5
COMPRESSOR



อะไหล่
WARRANTY 2
SPARE PART



MODEL:DCR-IV1



MODEL:CR-IV

INVERTER



100L1155-2557

100L1529-2561

100L2134-2553

INDOOR UNIT MODEL			DCR-125-IV1	DCR-185-IV1	DCR-255-IV1	DCR-305-IV1	DCR-305-3IV1
STANDARD NO.5							
AIR FLOW	CFM		400	600	800	1,000	1,000
POWER SUPPLY	V / Ph / Hz		220/1/50				
FAN	TYPE		CENTRIFUGAL DOUBLE INLET , DOUBLE WIDTH				
	QTY		2	2	2	2	2
MOTOR	TYPE		BLDC MOTOR				
	QTY		1	1	1	1	1
CONNECTION	SUCTION	INCH	1/2	1/2	5/8	5/8	5/8
	LIQUID	INCH	1/4	1/4	1/4	3/8	3/8
DIMENSION	WIDTH	CM	101.00	101.00	131.00	131.00	131.00
	HEIGHT	CM	64.00	64.00	64.00	64.00	64.00
	DEPTH	CM	21.00	24.00	24.00	27.00	27.00
APPROX WEIGHT	KG		28.00	32.00	45.00	48.00	48.00
OUTDOOR UNIT MODEL			CR-125-IV	CR-185-IV	CR-255-IV	CR-305-IV	CR-305-3IV
COOLING CAPACITY	BTU/HR.		12,681	19,000	25,066	30,168	31,091
	WATT บอ.2134		3,600	5,300	7,300	8,800	8,800
POWER INPUT	WATT บอ.1529		1,000	1,472	2,157	2,840	2,840
CURRENT	AMP.		2.5-7	3.5-8	4.5-13	5.5-15	2.5-8
SEER	BTU/WATT		19.76	17.78	17.44	16.62	17.30
COMPRESSOR	TYPE		TWIN ROTARY				
CONDENSER COIL	TYPE		COPPER TUBE AND ALUMINIUM FIN				
REFRIGERANT	TYPE		R32				
POWER SUPPLY	V / Ph / Hz		220/1/50	220/1/50	220/1/50	220/1/50	380/3/50
MOTOR	TYPE		PERMANENT SPLIT CAPACITY				
CONNECTION	SUCTION	INCH	1/2	1/2	5/8	5/8	5/8
	LIQUID	INCH	1/4	1/4	1/4	3/8	3/8
DIMENSION	WIDTH	CM	85.00	95.00	98.00	98.00	98.00
	HEIGHT	CM	54.50	69.50	79.50	79.50	79.50
	DEPTH	CM	28.50	37.00	39.00	39.00	39.00
APPROX WEIGHT	KG		32.00	42.00	55.00	57.00	61.00

Note : Cooling capacity base on 27 °C D.B., 19 °C W.B., Air on evaporator coil and 35 °C Ambient air for outdoor unit.
Specification subject to change without notice.

FLOOR & CEILING TYPE

AIR CONDITIONING



MODEL: DCR-IV / CR-IV



FILTER



4-SPEED FAN LEVELS



2 WAYS AUTO SWING



SLEEP MODE



TIMER



Standard

Option



คอมเพรสเซอร์ 5 ปี
อะไหล่ SPARE PART 2 ปี



MODEL:DCR-IV1



MODEL:CR-IV

INVERTER



100L1155-2557

100L1529-2561

100L2134-2553

INDOOR UNIT MODEL			DCR-335-IV1	DCR-335-3IV1	DCR-365-IV1	DCR-365-3IV1	DCR-405-IV1	DCR-405-3IV1
STANDARD NO.5								
AIR FLOW	CFM		1,100	1,100	1,200	1,200	1,350	1,350
POWER SUPPLY	V / Ph / Hz		220/1/50					
FAN	TYPE		CENTRIFUGAL DOUBLE INLET , DOUBLE WIDTH					
		QTY	4	4	4	4	4	4
MOTOR	TYPE		BLDC MOTOR			AC MOTOR		
		QTY	1	1	1	1	1	1
CONNECTION	SUCTION	INCH	5/8	5/8	5/8	5/8	5/8	5/8
	LIQUID	INCH	3/8	3/8	3/8	3/8	3/8	3/8
DIMENSION	WIDTH	CM	131.00	131.00	161.00	161.00	161.00	161.00
	HEIGHT	CM	64.00	64.00	64.00	64.00	64.00	64.00
	DEPTH	CM	27.00	27.00	24.00	24.00	24.00	24.00
APPROX WEIGHT	KG		54.00	54.00	58.00	58.00	58.00	58.00
OUTDOOR UNIT MODEL			CR-335-IV	CR-335-3IV	CR-365-IV	CR-365-3IV	CR-405-IV	CR-405-3IV
COOLING CAPACITY	BTU/HR.		34,402	33,987	37,465	38,041	40,298	40,157
	WATT มอก.2134		9,500	9,500	10,600	10,600	11,800	11,800
POWER INPUT	WATT มอก.1529		3,060	3,060	3,420	3,420	3,810	3,810
CURRENT	AMP.		6.5-16	2.5-8	6.5-18	2.5-8	7.5-21	3.5-9
SEER	BTU/WATT		16.38	16.51	16.89	16.62	16.14	16.17
COMPRESSOR	TYPE		TWIN ROTARY					
CONDENSER COIL	TYPE		COPPER TUBE AND ALUMINIUM FIN					
REFRIGERANT	TYPE		R32					
POWER SUPPLY	V / Ph / Hz		220/1/50	380/3/50	220/1/50	380/3/50	220/1/50	380/3/50
MOTOR	TYPE		PERMANENT SPLIT CAPACITY					
CONNECTION	SUCTION	INCH	5/8	5/8	5/8	5/8	5/8	5/8
	LIQUID	INCH	3/8	3/8	3/8	3/8	3/8	3/8
DIMENSION	WIDTH	CM	98.00	98.00	98.00	98.00	110.00	110.00
	HEIGHT	CM	79.50	79.50	79.50	79.50	110.50	110.50
	DEPTH	CM	39.00	39.00	39.00	36.00	40.00	40.00
APPROX WEIGHT	KG		57.00	61.00	57.00	61.00	77.00	80.00

Note : Cooling capacity base on 27 °C D.B., 19 °C W.B., Air on evaporator coil and 35 °C Ambient air for outdoor unit.
Specification subject to change without notice.

FLOOR & CEILING TYPE

AIR CONDITIONING



MODEL: DCR-31V / CR-31V



FILTER



4 -SPEED FAN
LEVELS



2 WAYS AUTO SWING



SLEEP MODE



TIMER



Standard



Option



MODEL:DCR-31V



MODEL:CR-31V

INVERTER



คอมเพรสเซอร์
COMPRESSOR



อะไหล่
SPARE PART



100.1529-2561

INDOOR UNIT MODEL			DCR-45-31V	DCR-48-31V	DCR-55-31V	DCR-60-31V
STANDARD NO.5						
AIR FLOW	CFM		1,500	1,600	1,800	2,000
POWER SUPPLY	V / Ph / Hz		220/1/50			
FAN	TYPE		CENTRIFUGAL DOUBLE INLET , DOUBLE WIDTH			
	QTY		4	4	4	4
MOTOR	TYPE		AC MOTOR			
	QTY		1	2	2	2
CONNECTION	SUCTION	INCH	5/8	5/8	3/4	3/4
	LIQUID	INCH	3/8	3/8	3/8	3/8
DIMENSION	WIDTH	CM	161.00	191.00	191.00	191.00
	HEIGHT	CM	64.00	64.00	64.00	64.00
	DEPTH	CM	27.00	27.00	27.00	31.50
APPROX WEIGHT	KG		58.00	80.00	86.00	95.00
OUTDOOR UNIT MODEL			CR-45-31V	CR-48-31V	CR-55-31V	CR-60-31V
COOLING CAPACITY	BTU/HR.		44,828	48,689	53,324	58,995
POWER INPUT	WATT		4,400	4,700	5,950	5,950
CURRENT	AMP.		4.5-11	4.8-13.5	4.8-15	5.5-16
SEER	BTU/WATT		15.87	15.87	15.46	16.14
COMPRESSOR	TYPE		TWIN ROTARY			
CONDENSER COIL	TYPE		COPPER TUBE AND ALUMINIUM FIN			
REFRIGERANT	TYPE		R32			
POWER SUPPLY	V / Ph / Hz		380/3/50			
MOTOR	TYPE		PERMANENT SPLIT CAPACITY			
CONNECTION	SUCTION	INCH	5/8	5/8	3/4	3/4
	LIQUID	INCH	3/8	3/8	3/8	3/8
DIMENSION	WIDTH	CM	110.00	110.00	110.00	110.00
	HEIGHT	CM	110.50	110.50	110.50	110.50
	DEPTH	CM	40.00	40.00	40.00	40.00
APPROX WEIGHT	KG		80.00	80.00	92.00	92.00

Note : Cooling capacity base on 27 °C D.B., 19 °C W.B., Air on evaporator coil and 35 °C Ambient air for outdoor unit.
Specification subject to change without notice.