

Online Series							
TAC-XAL							
Model		Indoor	TAC-XAL09C	TAC-XAL12C	TAC-XAL18C	TAC-XAL24C	
		Outdoor	TAC-XAL09H	TAC-XAL12H	TAC-XAL18H	TAC-XAL24H	
BTU			9490	12340	18580	24130	
Platform			770X(φ5×2)+650C(φ7×1)	770X(φ5×2)+660C(φ5×1)	900X(φ7×2)+780C(φ5×1)	1010X(φ7×2)+780C(φ5×2)	
Type			Cooling only	Cooling only	Cooling only	Cooling only	
Control type			Remote Control	Remote Control	Remote Control	Remote Control	
EGAT (Star)			5	5★	5	5	
SEER			17.84	18.70	18.02	17.37	
Rated cooling capacity		Btu/h	9490(2720~12350)	12340(3530~16050)	18580(5315~24160)	24130(6900~31380)	
		W	2770(795~3610)	3620(1040~4710)	5445(1560~7080)	7080(2030~9210)	
EER		Btu/h.w	11.90	10.67	10.49	10.57	
		W/W	3.49	3.13	3.07	3.10	
Indoor noise level at cooling	Turbo/High/Med/Low/Silent	dB(A)	42/40/38/35/32	44/42/20/38/35	47/45/42/40/38	49/47/45/42/40	
Outdoor noise level		dB(A)	54	54	56	56	
Power supply			220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P	
Voltage Range			V	165~265	165~265	165~265	
Rated current	Cooling	A	3.7(1.1~4.8)	5.4(1.5~7.0)	8.2(2.3~10.7)	10.6(3.0~13.8)	
Rated input	Cooling	W	795(225~1030)	1155(330~1500)	1770(505~2300)	2280(650~2970)	
Max current		A	4.8	7	10.7	13.8	
Max input		W	1030	1500	2300	2970	
Refrigerant/Charge			Gram	R32/400	R32/510	R32/690	
Compressor	Type		Rotary	Rotary	Rotary	Rotary	
	Model		KSK89D35UEZE3	KSK103D33UEZC3	GSD113RKQF6JV6B	KSN140D33UFZ3	
	MFG		GMCC	GMCC	HIGHLY	GMCC	
Indoor Moter type			AC	DC	DC	DC	
Outdoor Moter type			DC	DC	DC	DC	
Fan System							
Indoor air circulation		Cooling/heating	m³/h	450	500	810	1100
Indoor fan type				Cross flow	Cross flow	Cross flow	Cross flow
Outdoor fan type				Axial flow	Axial flow	Axial flow	Axial flow
Connection system							
Connecting Pipe	Gas	mm	9.52(3/8")	9.52(3/8")	12.7(1/2")	12.7(1/2")	
	Liquid	mm	6.35(1/4")	6.35(1/4")	6.35(1/4")	6.35(1/4")	
Connecting Wiring		Size x Core number	1.0mm²*4	1.0mm²*4	1.5mm²*4	1.5mm²*4	
Others							
Suitable area		m²	9~16	15~23	20~35	30~50	
Net dimensions	Indoor	mm	776×202×250	776×202×250	910×206×294	1010×220×315	
	Outdoor	mm	722×459×276	787×498×290	863×602×349	863×602×349	
Net weight	Indoor	kg	7.5	7.5	9.5	12	
	Outdoor	kg	19	21	26	28	
Packing dimensions	Indoor	mm	850×275×320	850×275×320	979×277×372	1096×297×390	
	Outdoor	mm	765×481×310	818×520×325	890×628×385	890×628×385	
Gross weight	Indoor	kg	10.5	10.5	12.5	15	
	Outdoor	kg	23	25	30	32	
Selfcleaning			Y	Y	Y	Y	
Barcode Indoor			6931084740503	6931084740527	6931084740541	6931084740565	
Barcode Outdoor			6931084740510	6931084740534	6931084740558	6931084740572	

ขอสงวนสิทธิ์ในการเปลี่ยนแปลงโดยไม่ต้องแจ้งให้ทราบล่วงหน้า