Haier

More Creation, More Possibilities

SUPERAIR

เย็นทั่วถึงทุกมุม อากาศสะอาดได้สุขภาพ
พร้อม Smart Control ที่สั่งการได้ทุกที่ทุกเวลา



SELF-CLEANING

แอร์ล้างตัวเองได้
ช่วยทำความสะอาด
แผงคอยล์เย็นให้สะอาด




SMART CONTROL

ควบคุมการทำงาน
เครื่องปรับอากาศจาก
ทุกที่ผ่านแอป Haismart



ANTIBACTERIAL FILTER

แผ่นกรองอากาศ
ช่วยยับยั้งแบคทีเรีย
ได้อย่างมีประสิทธิภาพ



HUMAN SENSOR (OPTIONAL)

เซนเซอร์อัจฉริยะ
ตรวจจับความเคลื่อนไหว
ช่วยประหยัดไฟสูงสุด



Ceiling Type

Inverter/R32

3D Airflow

Show Temperature and Error

DC Fan Motor

Copper 100%

WARRANTY COMPRESSOR 10 YEARS

รับประกันคอมเพรสเซอร์ 10 ปี
รับประกันตัวเครื่อง 5 ปี*

*ฟรีบริการรายการ 5 ปีแรก ตามเงื่อนไขบริษัท



มอก. 2134-2565 มอก. 1529-2561

แจ้งซ่อมที่ LINE OA บริการทุกวัน @haierthailand

HaierCare 1789

สีและรายละเอียดต่างๆ ที่ปรากฏในสื่อสิ่งพิมพ์นี้เป็นเพียงสินค้าตัวอย่าง ไฮเออร์สงวนสิทธิ์ในการเปลี่ยนแปลงสีโดยไม่แจ้งให้ทราบล่วงหน้า

บริษัท ไฮเออร์ อีเลคทริคอล แอพพลายแอนซ์ (ประเทศไทย) จำกัด
เลขที่ 90 อาคารซีดับเบิ้ลยู ทาวเวอร์ (ตึก เอ) ชั้นที่ 42-43
ถนนรัชดาภิเษก แขวงห้วยขวาง เขตห้วยขวาง กรุงเทพมหานคร 10310
www.haier.com/th | www.facebook.com/HaierThailand



18K, 25K, 30K



36K



42K, 48K, 60K



18K, 25K



30K, 36K



42K, 48K



60K



HW-SA201ABK
Optional



YL-HQS01
Standard



มอก. 2134-2565 มอก. 1529-2561

รับประกันคอมเพรสเซอร์ 10 ปี
รับประกันตัวเครื่อง 5 ปี*
*หรือรุ่นระยะ 5 ปีแรก ตามเงื่อนไขบริษัท





MODEL			SET	HCFI-18GSR32	HCFI-25GSR32	HCFI-30GSR32	HCFI-36GSR32	HCFI-36GTR32	HCFI-42GSR32	HCFI-42GTR32	HCFI-48GSR32	HCFI-48GTR32	HCFI-60GTR32
			Indoor	HCFI-18GSR32F	HCFI-25GSR32F	HCFI-30GSR32F	HCFI-36GSR32F	HCFI-36GTR32F	HCFI-42GSR32F	HCFI-42GTR32F	HCFI-48GSR32F	HCFI-48GTR32F	HCFI-60GTR32F
			Outdoor	1U-18S1R32CP	1U-25S1R32CP	1U-30S1R32CP	1U-36S1R32CP	1U-36T3R32CP	1U-42S1R32CP	1U-42T3R32CP	1U-48S1R32CP	1U-48T3R32CP	1U-60T3R32C
Rated Cooling	Cooling Capacity		Btu/h	18,500	25,000	30,000	35,500	36,000	44,000	42,000	48,000	50,000	58,000
	Cooling Capacity Min - Max		Btu/h	7,500-19,800	8,900-27,300	12,300-34,100	13,600-38,200	17,100-38,200	19,400-44,400	19,400-44,400	21,200-50,200	21,200-50,200	15,400-56,300
	Cooling Capacity		kW	5.30	7.30	8.80	10.50	10.50	12.10	12.10	14.10	14.10	16.00
	Power Input		kW	1.48	2.32	2.61	3.33	3.27	4.07	4.03	5.38	5.26	5.39
	Current		A	6.50	10.19	11.46	14.62	5.69	17.98	6.85	23.75	8.78	8.65
	SEER			18.46	17.81	19.11	16.51	17.30	18.66	18.28	17.61	17.26	17.13
	Energy Efficiency Level		/	5	5	5**	5	5*	5***	5**	5*	5**	5**
Indoor	Power Cable		/	/	/	/	/	/	/	/	/	/	/
Outdoor	Power Cable		mm²	3*2.5	3*2.5	3*2.5	3*4	5*2.5	3*6	5*2.5	3*6	5*2.5	5*2.5
Communication Cable※2			mm²	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5
Minimum Circuit Amps(MCA)			A	9.28	13.03	16.05	19.80	9.51	24.46	10.08	28.83	11.33	12.05
Maximum Fuse Amps(MFA)			A	16	16	20	25	16	32	16	40	16	16
Indoor Unit													
Power Supply			Ph/V/Hz	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply
Airflow Rate (SH/H/M/L/Q)	Cooling Mode		m³/h	1090/980/850/750/580	1400/1260/1050/880/700	1550/1400/1200/970/700	1600/1550/1320/1080/780	1600/1550/1320/1080/780	2050/1850/1600/1400/1280	2050/1850/1600/1400/1280	2150/2050/1800/1480/1050	2150/2050/1800/1480/1050	2250/2000/1600/1280/950
			CFM	641/576/500/441/341	824/741/618/518/412	912/824/706/571/412	941/912/776/635/459	941/912/776/635/459	1206/1088/980/850/754	1206/1088/980/850/754	1267/1255/1137/997/761	1267/1255/1137/997/761	1324/1177/942/753/559
Sound Pressure Level (SH/H/M/L/Q)			dB(A)	43/40/38/35/30	43/40/38/35/30	46/43/41/37/30	46/43/41/37/31	46/43/41/37/31	46/43/41/38/36	46/43/41/38/36	48/46/43/40/33	48/46/43/40/33	48/46/43/40/33
Dimension	Net Dimension (W*D*H)		mm	1000*230*680	1000*230*680	1325*230*680	1325*230*680	1325*230*680	1650*230*680	1650*230*680	1650*230*680	1650*230*680	1650/230/680
	Package Dimension (W*D*H)		mm	1100*305*779	1100*305*779	1425*305*779	1425*305*779	1425*305*779	1750*305*779	1750*305*779	1750*305*779	1750*305*779	1750/305/779
Net/Gross Weight			kg	26/32	27/33	34/42	34/42	34/42	43/51	43/51	43/51	43/51	43/51
Air Filter Material			/	PET (Antibacterial)	PET (Antibacterial)	PET (Antibacterial)	PET (Antibacterial)	PET (Antibacterial)	PET (Antibacterial)	PET (Antibacterial)	PET (Antibacterial)	PET (Antibacterial)	PET (Antibacterial)
Drainage Pipe (Material, Dimension)			mm	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25
Controller(Standard)			/	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01
Controller(Optional)			/	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK
WIFI Module (Standard)			/	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI
Outdoor Unit													
Power Supply			V/Ph/Hz	220/1/50	220/1/50	220/1/50	220/1/50	380/3/50	220/1/50	380/3/50	220/1/50	380/3/50	380/3/50
Compressor	Type		/	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary
Max. Outdoor Airflow Rate			m³/h	2500	2500	3500	3800	5300	5500	5500	5500	5500	7400
			CFM	1475	1475	2064	2240	3136	3250	3250	3250	3250	4363
Max. Outdoor Sound Pressure Level			dB(A)	54	54	57	59	56	58	58	57	57	59
Electrical Control Box IP Class			/	IP44	IP44	IP44	IP44	IP44	IP44	IP44	IP44	IP44	IP44
Dimension	Net Dimension (W*D*H)		mm	820*300*615	820*300*615	920*372*765	920*372*765	920*372*765	950*370*965	950*370*965	950*370*965	950*370*965	950*370*1350
	Package Dimension (W*D*H)		mm	977*400*735	977*400*735	1070*472*808	1070*472*808	1023*465*825	1050*485*1130	1050*485*1130	1050*485*1130	1050*485*1130	1050*485*1500
Outdoor Net/Gross Weight			kg	38/42	38/42	52/57	52/57	54/59	62/74	65/77	65/77	62/74	101/116
Refrigerant	Type		/	R32	R32	R32	R32	R32	R32	R32	R32	R32	R32
	GWP		/	675	675	675	675	675	675	675	675	675	675
	Default Refrigerant Charge		kg	1.00	1.16	1.31	1.53	1.65	1.90	1.90	1.90	1.90	3.50
	Control Method		/	Capillary Tube	Capillary Tube	Capillary Tube	Capillary Tube	Electronic Expansion Valve	Electronic Expansion Valve	Electronic Expansion Valve	Electronic Expansion Valve	Electronic Expansion Valve	Electronic Expansion Valve
Refrigerant Pipe	Liquid Pipe OD. Diameter (Connection Method)		mm	Ø6.35 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)
	Gas Pipe OD. Diameter (Connection Method)		mm	Ø12.70 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø19.05 (Flared)
	Max. Single Way Pipe Length between Indoor and Outdoor Unit		m	20	20	25	30	50	50	50	50	50	70
	Max. Height Difference between Indoor and Outdoor Unit		m	10	10	10	20	30	30	30	30	30	30
	Min. Single Way Pipe Length between Indoor and Outdoor Unit		m	5	5	5	5	5	5	5	5	5	5
	Max. Pipe Length without Charging Refrigerant		m	10	10	15	15	30	30	30	30	30	15
	Additional Refrigerant Charging Amount		g/m	20	35	35	35	35	35	35	35	35	45
Working Temperature		Cooling(Min.~Max.)	°C DB	18~43	18~43	18~43	18~43	18~43	18~43	18~43	18~43	18~43	18~43

※1 Rated condition: Indoor temperature(cooling): 27°C DB/19°C WB, Outdoor temperature(cooling): 35°CDB/24°CWB. / The data is measured with 5m equivalent pipe and 0m height difference.
※2 Indoor and outdoor communication cable: If communication cable length ≤40m, communication cable: 2.5mm² / If 40m<the communication cable length ≤55m, communication cable: 4mm² / If 55m<the communication cable length ≤75m, communication cable: 6mm²