Haier
More Creation, More Possibilities

SUPERAIR

สัมผัสความเย็น 360° ด้วยลมเย็นอิสระ 4-Way Independent

พร้อมประหยัดไฟ ให้ทุกองศาคุ้มค่ากว่าเดิม



SELF-CLEANING
แอร์ล้างตัวเองได้
ช่วยทำความสะอาด
แผงคอยล์เย็นให้สะอาด


4-WAY INDEPENDENT AIRFLOW
สวิงมอเตอร์แยกอิสระ ควบคุม
ทิศทางลมเย็นได้ตามต้องการ



360° AIRFLOW
กระจายความเย็นรอบตัว
ทำให้สบายทุกมุมห้อง
โดยไร้จุดอับความเย็น



100% COPPER AIR PIPE
ท่อน้ำยา ทองแดง 100%
มีประสิทธิภาพในการถ่ายเท
ความร้อนได้สูงขึ้น 30-50%



Round Flow Premium
Cassette Type
Inverter/R32

- Innovative 4 Independent Airflow Control
- Max. 4.5m High Ceiling Mode
- Auto Swing Wide Discharge Angle: 20°to 70°
- Panel Convenient Clip

รับประกันคอมเพรสเซอร์ 10 ปี
รับประกันตัวเครื่อง 5 ปี*
*ฟรีทุกรายการ 5 ปีแรก ตามเงื่อนไขบริษัท

มอก. 2134-2565 มอก. 1529-2561

แจ้งซ่อมที่ LINE OA บริการทุกวัน @haierthailand

Haier Care 1789

สีและรายละเอียดต่างๆที่ปรากฏในสื่อสิ่งพิมพ์นี้เป็นเพียงภาพประกอบเท่านั้น อาจมีความแตกต่างจากสินค้าตัวจริง ไฮเออร์สงวนสิทธิ์ในการเปลี่ยนแปลงสเปคโดยไม่ต้องแจ้งให้ทราบล่วงหน้า

บริษัท ไฮเออร์ อีเลคทริคอล แอพพลายแอนซ์ (ประเทศไทย) จำกัด
เลขที่ 90 อาคารซีดับเบิ้ลยู ทาวเวอร์ (ตึก เอ) ชั้นที่ 42-43
ถนนรัชดาภิเษก แขวงห้วยขวาง เขตห้วยขวาง กรุงเทพมหานคร 10310
www.haier.com/th | www.facebook.com/HaierThailand



18K



25K



30K, 36K



42K, 48K, 60K



18K, 25K



30K, 36K



42K, 48K



60K



HW-SA201ABK
Optional



YL-HQS01
Standard



มอก. 2134-2565 มอก. 1529-2561



รับประกันคอมเพรสเซอร์ 10 ปี
รับประกันตัวเครื่อง 5 ปี*
*พิจารณาตาม 5 มีนา เงื่อนไขบริษัท



MODEL		SET	HCSI-18PSR32	HCSI-25GSR32	HCSI-30GSR32	HCSI-36GSR32	HCSI-36GTR32	HCSI-42GSR32	HCSI-42GTR32	HCSI-48GSR32	HCSI-48GTR32	HCSI-60GTR32
		Indoor	HCSI-18PSR32F	HCSI-25GSR32F	HCSI-30GSR32F	HCSI-36GSR32F	HCSI-36GTR32F	HCSI-42GSR32F	HCSI-42GTR32F	HCSI-48GSR32F	HCSI-48GTR32F	HCSI-60GTR32F
		Outdoor	1U-18S1R32CP	1U-25S1R32CP	1U-30S1R32CP	1U-36GSR32CP	1U-36T3R32CP	1U-42S1R32CP	1U-42T3R32CP	1U-48S1R32CP	1U-48T3R32CP	1U-60T3R32C
Rated Cooling	Cooling Capacity	Btu/h	19,000	26,500	30,500	35,500	38,500	46,000	46,000	48,000	49,000	54,000
	Cooling Capacity Min - Max	Btu/h	6,800-20,100	9,600-27,300	11,900-33,800	13,600-38,900	13,600-40,300	15,400-42,000	15,400-42,000	17,700-48,100	17,700-48,100	15,400-54,600
	Capacity	kW	5.30	7.30	8.80	10.50	10.50	12.10	12.10	14.10	14.10	15.00
	Power Input	kW	1.48	2.32	2.64	3.33	3.20	4.35	4.03	5.34	5.22	5.03
	Current	A	6.80	10.19	11.59	14.62	5.57	19.22	6.85	23.58	8.71	8.07
	SEER		19.31	18.60	18.94	17.16	16.92	17.71	17.03	16.55	15.90	16.62
	Energy Efficiency Level		5★	5★	5★★	5★	5	5★★	5★★	5★	5★	5★
Indoor	Power Cable	/	/	/	/	/	/	/	/	/	/	/
Outdoor	Power Cable	mm^2	3*2.5	3*2.5	3*2.5	3*4	5*2.5	3*6	5*2.5	3*6	5*2.5	5*2.5
Communication Cable※2		mm^2	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5	4*2.5
Minimum Circuit Amps (MCA)		A	9.27	13.14	16.02	19.77	9.52	24.62	10.25	29.62	11.50	12.23
Maximum Fuse Amps (MFA)		A	16	16	20	25	16	32	16	40	16	16
Indoor Unit												
Power Supply		Ph/V/Hz	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply	Outdoor Unit Power Supply
Airflow Rate (SH/H/M/L/Q)	Cooling Mode	m^3/h	760/700/620/500/500	1450/1250/1050/900/650	1750/1590/1350/1045/800	1800/1640/1400/1150/820	1800/1640/1400/1150/820	2000/1700/1500/1300/1000	2080/1780/1580/1400/1000	2035/1910/1635/1450/950	2035/1910/1635/1450/950	2150/1910/1635/1500/800
		CFM	447 / 412 / 365 / 294	853 / 735 / 618 / 529 / 382	1029 / 935 / 794 / 615 /471	1059 / 965 / 824 / 676 / 482	1059 / 965 / 824 / 676 / 482	1176 / 1000 / 882 / 765 / 588	1176 / 1000 / 882 / 765 / 588	1197 / 1124 / 962 / 853 / 559	1197 / 1124 / 962 / 853 / 559	1266 / 1124 / 962 / 883 / 471
Sound Pressure Level(SH/H/M/L/Q)		dB(A)	40/37/35/32/32	47/44/41/36/31	51/49/45/40/33	53/52/48/45/37	53/52/48/45/37	52/49/45/41/37	52/49/45/41/37	53/51/47/43/37	53/51/47/43/37	55/51/47/45/35
Dimension	Net Dimension (W*D*H)	mm	870*870*260	840*840*204	840*840*246	840*840*246	840*840*246	840*840*288	840*840*288	840*840*288	840*840*288	840/840/288
	Package Dimension (W*D*H)	mm	718*680*380	990*990*310	978*978*269	978*978*269	978*978*269	978*978*353	978*978*353	978*978*353	978*978*353	978/978/353
Net/Gross Weight		kg	19/22	23/28	24/31	24/31	24/31	27/33	27/33	27/33	27/33	27/33
Drainage Pipe (Material, Dimension)		mm	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25	PVC DN25
Pump Head		mm	1200	1200	1200	1200	1200	1200	1200	1200	1200	1200
Controller(Standard)		/	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01
Controller(Optional)		/	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK	HW-SA201ABK
WIFI Module (Standard)		/	-	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI	HI-WA101DEI
Panel	Panel Model (Standard)	/	PB-620KB	PB-950QB	PB-950QB	PB-950QB	PB-950QB	PB-950QB	PB-950QB	PB-950QB	PB-950QB	PB-950QB
	Net Dimension(W*D*H)	mm	620*620*60	950*950*50	950*950*50	950*950*50	950*950*50	950*950*50	950*950*50	950*950*50	950*950*50	950*950*50
	Package Dimension(W*D*H)	mm	660*660*115	1000*1000*110	1000*1000*110	1000*1000*110	1000*1000*110	1000*1000*110	1000*1000*110	1000*1000*110	1000*1000*110	1000*1000*110
	Net/Gross Weight	kg	2.8/4.5	5.5/8.5	5.5/8.5	5.5/8.5	5.5/8.5	5.5/8.5	5.5/8.5	5.5/8.5	5.5/8.5	5.5/8.5
	Swing Angle	°	20~70	20~70	20~70	20~70	20~70	20~70	20~70	20~70	20~70	20~70
Outdoor Unit												
Power Supply		V/Ph/Hz	220/1/50	220/1/50	220/1/50	220/1/50	380/3/50	220/1/50	380/3/50	220/1/50	380/3/50	380/3/50
Compressor	Type	/	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary
Max. Outdoor Airflow Rate		m^3/h	2500	2500	3500	3800	5300	5500	5500	5500	5500	7400
		CFM	1475	1475	2064	2240	3136	3250	3250	3250	3250	4363
Max. Outdoor Sound Pressure Level		dB(A)	54	54	57	59	56	58	58	57	57	59
Electrical Control Box IP Class		/	IP44	IP44	IP44	IP44	IP44	IP44	IP44	IP44	IP44	IP44
Dimension	Net Dimension (W*D*H)	mm	820*338*614	820*300*615	920*372*765	920*372*765	920*372*765	950*370*965	950*370*965	950*370*965	950*370*965	950*370*1350
	Package Dimension (W*D*H)	mm	977*400*735	977*400*735	1085*487*843	1085*487*843	1023*465*825	1050*485*1130	1050*485*1130	1050*485*1130	1050*485*1130	1050*485*1500
Outdoor Net/Gross Weight		kg	38/42	38/42	52/57	52/57	54/59	62/74	65/77	65/77	62/74	101/116
Refrigerant	Type	/	R32	R32	R32	R32	R32	R32	R32	R32	R32	R32
	GWP	/	675	675	675	675	675	675	675	675	675	675
	Default Refrigerant Charge	kg	0.97	1.16	1.31	1.53	1.65	1.90	1.90	1.90	1.90	3.50
	Control Method	/	Capillary Tube	Capillary Tube	Capillary Tube	Capillary Tube	Electronic Expansion Valve	Electronic Expansion Valve	Electronic Expansion Valve	Electronic Expansion Valve	Electronic Expansion Valve	Electronic Expansion Valve
Refrigerant Pipe	Liquid Pipe OD. Diameter (Connection Method)	mm	Ø6.35 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)	Ø9.52 (Flared)
	Gas Pipe OD. Diameter (Connection Method)	mm	Ø12.70 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø15.88 (Flared)	Ø19.05 (Flared)
	Max. Single Way Pipe Length between Indoor and Outdoor Unit	m	20	20	25	30	50	50	50	50	50	70
	Max. Height Difference between Indoor and Outdoor Unit	m	10	10	10	20	30	30	30	30	30	30
	Min. Single Way Pipe Length between Indoor and Outdoor Unit	m	5	5	5	5	5	5	5	5	5	5
	Max. Pipe Length without Charging Refrigerant	m	10	10	15	15	30	30	30	30	30	15
	Additional Refrigerant Charging Amount	g/m	20	35	35	35	35	35	35	35	35	45
Working Temperature	Cooling(Min.~Max.)	°C DB	18~43	18~43	18~43	18~43	18~43	18~43	18~43	18~43	18~43	18~43

※ 1 Rated condition: Indoor temperature(cooling): 27°C DB/19°C WB, Outdoor temperature(cooling): 35°CDB/24°CWB. / The data is measured with 5m equivalent pipe and 0m height difference.
※ 2 Indoor and outdoor communication cable: If communication cable length ≤40m, communication cable: 2.5mm² / If 40m<the communication cable length ≤55m, communication cable: 4mm² / If 55m<the communication cable length ≤75m, communication cable: 6mm²